

# Tianjin



## END SUCTION CENTRIFUGAL PUMPS

A wide range of stainless steel and cast iron pumps available to cover a multitude of applications in the domestic, industrial and agricultural market.



### SWB Series

**AISI 304** threaded stainless steel pumps for domestic and industrial applications.

Delivery: up to 260 L/min  
Head: up to 62 m  
Available in: 220 V up to 1.85 kW  
380 V up to 1.85 kW



### SHS Series

**AISI 304 or 316** (on request) horizontal multistage pumps for domestic and industrial applications.

Delivery: up to 22 m<sup>3</sup>/h  
Head: up to 54 m  
Available in: 220 V up to 2.2 kW  
380 V up to 3 kW



### SJETS Series

Self-priming centrifugal pumps.

Max. total lift: up to 8 m  
Delivery: up to 3 m<sup>3</sup>/h  
Head: up to 47 m  
Available in: 220 V and  
380 V up to 0.75 kW



### SXR Series

Inline circulators for hot water and air conditioning cooling systems. 3-Speed operation

Delivery: up to 120 L/min  
Head: up to 12 m  
Pipe Size: 15 to 50mm  
Available in: 220 V and  
380 V up to 280 watts



### SGA Series

**AISI 316** Flanged stainless pumps to EN733 (DIN 24255) for moderately aggressive liquids.

Delivery: up to 72 m<sup>3</sup>/h  
Head: up to 58 m  
Available in: 380 V up to 15 kW  
220 V up to 2.2 kW on request



### SCA Series

Centrifugal pumps with cast iron body and impeller Flanged with threaded counter flanges to EN733 (DIN 24255).

Delivery: up to 225 m<sup>3</sup>/h  
Head: up to 90 m  
Available in: 380 V up to 37 kW  
220 V up to 2.2 kW on request

## MULTISTAGE PUMPS

### SMS Series

Vertical multistage pumps, in **AISI 304 or 316** (on request) stainless steel for water treatment, light industry, civil and agricultural applications.

Delivery: up to 110 m<sup>3</sup>/h  
Head: up to 300 m  
Available in: 380 V up to 45 kW  
220 V up to 2.2 kW on request



## SUBMERSIBLE DRAINAGE AND SEWAGE PUMPS

A submersible pump range to cover small to medium size applications.

### QDX Series

Submersible drainage pumps in **AISI 304** stainless.

Solids: up to 10 mm  
Delivery: up to 20 m<sup>3</sup>/h  
Head: up to 30 m  
Available in: 220 V with floatswitch,  
380 V up to 0.75 kW



### WQ Series

Submersible pumps in **AISI 304** stainless, designed to handle suspended solids.

Solids: up to 40 mm  
Delivery: up to 24 m<sup>3</sup>/h  
Head: up to 12 m  
Available in: 220 V with float switch  
380 V up to 1.1 kW



### SVN Series

Submersible pumps in **AISI 304** stainless for dirty water.

Delivery: up to 24 m<sup>3</sup>/h  
Head: up to 22 m  
Available in: 220 V with float switch  
380 V up to 1.5 kW



### SVQ/WQ Series

Submersible pumps designed to handle entrained solids waste water, sewage.

Solids: up to 50 mm  
Delivery: up to 36 m<sup>3</sup>/h  
Head: up to 22 m  
Available in: 220 V with float switch  
380V up to 2.2 kW

